



**DECLARATION OF PERFORMANCE  
DoP-1092-131112**

**HaTelit  
XP 50**

EN 15381

**Intended function(s): Reinforcement**

**HUESKER Synthetic GmbH  
Fabrikstraße 13–15  
48712 Gescher, Deutschland  
Tel. +49 (0) 25 42 / 701 - 0  
Fax. +49 (0) 25 42 / 701 – 499  
E-Mail: info@HUESKER.de  
Factory A**

System 2+

**Notified body No. 0799 Kiwa MPA Bautest GmbH, Niederlassung TBU Greven performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control.**

Essential characteristics	Performance	Harmonised technical specification
Tensile strength $T_{max}$ (EN ISO 10319)	MD 50 kN/m (- 0 kN/m) CMD 50 kN/m (- 0 kN/m)	EN15381 : 2008
Elongation $\epsilon_{max}$ (EN ISO 10319)	MD 5 % ( $\pm 1$ %) CMD 5 % ( $\pm 1$ %)	
Durability (Annex B)	To be covered within one day of installation.	

Gescher 01.07.2013

  
\_\_\_\_\_  
Helko Pintz  
(Manager Quality Assurance)